

Coming Soon



Order Code
Commander-1



Order Code
Commander-2



TECHNICAL DATA

Microphone:
 Directivity: Unidirectional
 Impedance: 1.0kΩ
 Sensitivity: -49±3dB (0dB=1V/Pa)
 Frequency Range: 100-16,000Hz
 Operating Temp: -20°C~+60°C
 Storage Temp: -25°C~+70°C

Speaker:
 Size: ø30 mm
 Input Power: 50 mW (1.26V)
 Max Power: 100 mW (1.79V)
 Impedance: 32Ω±10% at 1kHz, 0.18V
 Sound Pressure: 122±3dB at 1kHz
 Resonance Frequency: 150±30 (20%) Hz
 Frequency Range: 20Hz ~ 20,000Hz
 Operating Temp: -25°C ~ +50°C
 Storage Temp: -25°C ~ +50°C



USB-A



LEATHERETTE CUSHION



Commander

Universal 'Plug & play' USB professional office and contact centre headset, compatible with all major softphones. Fitted with 60mm leatherette ear cushions and padded T-bar, suitable for regular phone users.

Overview

Features	Single or dual speakers
	Left / right speaker side compatible
	Stereo audio sound for music and mono audio for speech
	Surround Shield™ noise cancelling microphone
	Fully flexible microphone for exact positioning
	270° adjustable microphone boom
	'Put and stay' ratchet microphone boom arm
	Swivel T-bar with padded leatherette cushion
	Overhead, padded sure-fit fully adjustable headband
What's included	Headset fitted with 60mm leatherette ear cushions and supplied with Quick Start Guide
Headset Weight	~ 54g / ~ 80g
Connection	USB-A direct plug-in
Certifications	FCC, CE, RoHS, REACH
Warranty	2 Years repair or replacement warranty
MOQ	Master Shipping Carton: 60
EAN:	Commander-1: 5060126958659, Commander-2: 5060126958673
SKU:	Commander-1: 575-344-001, Commander-2: 575-344-002

In-line Control Features

- 3 button in-line control with volume and mute
- 'Plug & Play' solution - No software download needed
- User will know the buttons by feel as each button will feel different
- Ribbing on the side of the control box to indicate the direction of the buttons
- LED illumination for power and in-use

