



## VIDEO CONFERENCING, MEET RADICAL SIMPLICITY

### **BENEFITS**

- Get any small or medium room up and running in minutes, with a simple setup process and all-in-one design
- Make it easy for anyone, even guests, to share content wirelessly from any personal device—with no special apps or tools needed
- Powerful audio pickup and incredible noise blocking technology allows every word to be heard without distractions
- On-board support for cloud service platforms means no room PC or Mac is required

### **POLY STUDIO X50**

The Poly Studio X50 video bar delivers radical simplicity in a small, elegant package. In small- and medium-sized rooms, connect easily with whatever video collaboration software you may use. Experience full boardroom-quality audio, advanced camera capabilities, and quick wireless content—all in one sleek video bar. And say goodbye to unnecessary pucks, cords, and cables, along with the PC or Mac to drive the meeting, since the Poly Video OS runs the show. Easy to install, easy to manage.

- Ideal for rooms of up to 10 participants
- Surround everyone with the rich, legendary sound with stereo speakers that deliver immersive, room-filling audio
- Dual monitor support ensures you have the ideal setup for many types of rooms
- Be heard clearly with our next generation microphone array

# **POLY**

## **STUDIO X50**



### **SPECIFICATIONS**

#### **PRODUCT SPECIFICATIONS**

Package includes:

- Poly Studio X50
- Cable bundle
- Wall mount
- Privacy cover

#### **VIDEO STANDARDS AND PROTOCOLS**

- H.264 AVC, H.264 High Profile, H.265

#### **VIDEO INPUT**

- 1x HDMI

#### **VIDEO OUT**

- 2x HDMI
- Touch display compatible

#### **PEOPLE VIDEO RESOLUTION**

- 4K, 30 fps (TX and RX) from 2048 Kbps
- 1080p, 60 fps from 1740 Kbps
- 1080p, 30 fps from 1024 Kbps
- 720p, 60 fps from 832 Kbps
- 720p, 30 fps from 512 Kbps

#### **CONTENT VIDEO RESOLUTION**

- Input
  - UHD (3840 x 2160)
  - HD (1920 x 1080p)
  - WSXGA+ (1680 x 1050)
  - UXGA (1600 x 1200)
  - SXGA (1280 x 1024)
  - WXGA (1280 x 768)
  - HD (1280 x 720p)
  - XGA (1024 x 768)
  - SVGA (800 x 600)

- Output
  - UHD (3840 x 2160)
  - WUXGA (1920 x 1200)
  - HD (1920 x 1080)
  - WSXGA+ (1680 x 1050)
  - SXGA+ (1400 x 1050)
  - SXGA (1280 x 1024)
  - HD (1280 x 720)
  - XGA (1024 x 768)
- Content frame rate
  - 5–60 fps (up to 4K resolution at 15 fps in call)

#### **CONTENT SHARING**

- Poly content app
- Apple Airplay
- Miracast
- HDMI input
- Whiteboarding

#### **CAMERA**

- 5x digital zoom
- 120° FOV
- UHD 2160p (4K) capture resolution
- Automatic people framing

#### **AUDIO INPUT**

- 3x MEMS microphones, plus 2x 2nd order microphones
- 1x HDMI
- 1x 3.5 mm line-in\*

#### **AUDIO OUTPUT**

- Stereo speakers
- 1x 3.5 mm line-out\*

#### **OTHER INTERFACES**

- 2x USB-A (3.0)
- 1x USB-C
- Bluetooth 5.0
- WiFi 802.11a/b/g/n/ac (MIMO) Multi-channel Concurrency

#### **AUDIO STANDARDS AND PROTOCOLS**

- 22 kHz bandwidth with Polycom Siren 22 technology, AAC-LD (TIP calls), G.719
- 14 kHz bandwidth with Polycom Siren 14 technology, G.722.1 Annex C
- 7 kHz bandwidth with G.722, G.722.1
- 3.4 kHz bandwidth with G.711, G.728, G.729A

#### **NETWORK**

- IPv4
- 1x 10/100/1G Ethernet
- Auto-MDIX
- H.323 and/or SIP up to 6 Mbps running Poly Video App
- Polycom Lost Packet Recovery (LPR) technology
- Dynamic bandwidth allocation
- Reconfigurable MTU size
- Web proxy support—Basic, Digest, and NTLM
- Simple Certificate Enrollment Protocol (SCEP)

# **POLY**

## **STUDIO X50**



### **SECURITY**

- Media encryption (H.323, SIP): AES-128, AES-256
- H.235.6 support
- Authenticated access to admin menus, web interface, and API
- Local account password policy configuration
- Security profiles
- Local account and login port lockout
- Secure defaults
- Remote logging with support for TLS
- Active directory external authentication

### **OPTIONS**

- VESA and wall mount kit
- Stand
- Poly TC8

### **INTEROPERABILITY**

- Support for native 3rd party applications, including Zoom Rooms for Android
- All cloud service provider through Poly Video App Mode

### **ELECTRICAL**

- Auto sensing power supply
- Typical operating voltage/power
  - 37 VA @ 120 V @ 60 Hz
  - 37 VA @ 230 V @ 50/60 Hz
- Typical BTU/h: 65

### **ENVIRONMENTAL SPECIFICATION**

- Operating temperature: 0 to 40 °C
- Operating humidity (non-condensing): 15 to 80%
- Non-operating temperature: -40 to 70 °C
- Non-operating humidity (non-condensing): 5 to 95%
- Maximum altitude: 16,000 ft

### **PHYSICAL CHARACTERISTICS**

- 30 W x 4 H x 4 D (Inches)  
762 W x 102 H x 102 D (MM)
- 5.6 lbs/2.54 kg

### **WARRANTY**

- One-year return to factory parts and labor

---

\*Supported in future software update

Some features may only be available with certain native apps or in Poly video mode

### **LEARN MORE**

For more information on Poly Studio X50, visit [poly.com/studiox](https://poly.com/studiox)